

138 Uptown™



- Aesthetically appealing squares design provides functionality for drying and retaining moisture and debris, while offering an upscale look.
- This rich carpet design is crush resistant and has very good dirt hiding characteristics.
- A dense heavyweight vinyl backing ensures longevity and minimum movement.
- Colors correspond and can be used together as a scrape & dry matting system with art.139 Boulevard.
- Suitable for heavy traffic conditions.
- For placement inside entrances in offices, hotels, banks, professional buildings restaurants, department stores.
- Vacuum or use extraction method to clean.
- Free of toxic DOP and DMF.



138 Uptown™

PRODUCT SPECIFICATIONS			
Designation	Dust Control Matting		
Description	Absorbent carpet mat		
Material			
	Top	Loop pile carpet densely tufted high-low pattern of 100% Decalon® yarns. 1270 grams of yarns per m².	
	Backing	Black vinyl	
Process	Tufted		
Category	Indoor absorbent - Upscale		
Recommended use	Indoor - heavy traffic conditions		
Colours	Brown, Charcoal, Navy Blue, Red, Green		
Weight	4 kg/m²		
Thickness	9.5 mm		
Standard sizes	60 cm x 90 cm 90 cm x 150 cm 120 cm x 180 cm 120 cm x 18.3 m 180 cm x 18.3 m		
Custom sizes	120 cm and 180 cm per linear meter		
Special remarks			
PRODUCT TESTING			
Tests	Norms	Results	
Abrasion resistance	ASTM D3884		
Colour fastness to light	AATCC 16E		
Accelerated wear test by sim floor machine	U.S.	3	
Accelerated soiling	U.S.	4.5	
Anti-slip	DIN51130 BGR181		
Water retention	U.S.	5.4 l/m²	
Sanitary epidemiologic test	GN 2.1.6.1338-03 MCL GN 2.1.6.2309-07 OBUV	Pass - Certificate no. 77.01.16.229.P.044984.07.09	
Resistance to delamination of the second backing	D3936-02	N/A	
Hardness of backing	D2240-02	70 Shore A	
Operation of the hexapod tumble drum tester	ASTM D5252-98a	Appearance 3.0 Color change 3.5	
Breaking load	D412	65.2 lb	
Elongation		33.6 %	
Standard test method for tuft bind of pile yarn floor covering	ASTM D1335-98	10.4 lb	
FIRE TESTING			
	Surface Flammability	ASTM D2859	Pass
	Classification of the reaction to fire performance	DIN EN 13501-1	
Sustainability	<ul style="list-style-type: none"> • Recyclable material • REACH compliant (Registration, Evaluation, Authorization and restrictions of Chemicals) • Contributes to cleaner environment by reducing need of cleaning chemicals 		