

























Specificatiile produsului			PIONIEER
Perioada de garantie	15		
Clasa de trafic	PN-EN ISO 10874		34/43
Grosime totala	PN-EN ISO 24346		2,50 mm
Grosimea stratului de uzura	PN-EN ISO 24340		0,70 mm
Greutate	PN-EN ISO 23997		2,25 kg/m <sup>2</sup>
Clasa de ignifugare	PN-EN 13501-1		B <sub>fl</sub> -s1
Rezistenta la alunecare	PN-EN 13893		≥ 0,3 DS
Rezistenta la alunecare	DIN 51130		R10 / R11 (depending on the calander type)
Proprietati electrice	PN-EN 14041		Antistatic and dissipating
Rezistenta electrica	PN-EN 1081		< 1,0 x 10 <sup>9</sup> Ω
Izolatie fonica	PN - EN ISO 717-2		18 dB
Indentare reziduala	PN-EN ISO 24343-1		≤ 0,20 mm
Rezist. la scaunul cu rotile	PN-EN 425		Fără daune vizibile
Rezistenta la chimicale	PN-EN ISO 26987		Odporna Resistant
Antistatizare	PN-EN 1815		< 2,0 kV
Rezistenta la uzura	PN-EN 651		T
Binder content	PN-EN ISO 10582	-	-
Rezistena la lumina	PN EN ISO 105-B02		min. 6
Stabilitate dimensionala	PN-EN ISO 23999		max 0,4 %
Dimensiune rolei	PN-EN ISO 24341		100 m <sup>2</sup> / 90 m <sup>2</sup> / 50 m <sup>2</sup>
Latimea rolei	PN-EN ISO 24341		4 m / 3 m / 2 m
Rezistenta termica R	PN-EN 12667		0,028 m <sup>2</sup> K/W
Incalzire sub pardoseala	-	-	de la 27°C pana la 27°C
Emisii VOC	PN-EN 16516		0,64 mg/m <sup>3</sup>
Formaldehyde	PN-EN 16516		E1
Carapace poliuretan PUR	-		da
Embossing INVERTECH	-		da
Toate informatiile prezentate mai sus sunt conforme cu cele prezentate de producator			
IROM ,strada Feleacu nr. 2,sector 1 ,Bucuresti			
<a href="http://www.irom.ro">www.irom.ro</a>			