

# 661 Cushion Ease Solid™ ESD Nitrile FR

ESD Nitrile FR modular mat



# Ergonomic, Anti-fatigue & Safety Matting - Dry Areas Modular Matting 661 Cushion Ease Solid™ ESD Nitrile FR

Ergonomic benefit derived from a 19 mm thick worker platform with a closed anti-slip pebble structure surface for maximum anti-fatigue comfort in dry industrial environments.

- Heavy duty rubber tiles can be easily assembled for coverage of large areas or individual workstations, wall-to-wall or as islands
- Compatible with patented MD Ramp System™ for smart safety bevelling solutions; allow out and inside corners
- Resistant to most industrial oils and suitable for welding areas

#### Recommended use

- Dry Areas
- For placement in ESD assembly lines, picking, packing and logistics warehouses, individual work stations.
- Heavy duty

#### Colors:

- Black

#### Sizes:

- 91cm x 91cm
- per m2

#### Accessories:

- 552 MD-X Ramp System™ Nitrile
- INS INSTALLATION
- 551 MD Ramp System™ Nitrile
- 057 ESD Mat Cleaner
- 056 ESD Wrist Band
- 052 ESD Common Grounding Cord
- 055 ESD Heel Grounder
- 051 ESD Floor Grounding Cord
- 054 ESD Earth Bonding Plug
- 053 ESD Coil Cord



#### SLIP RESISTANCE



# Ergonomic, Anti-fatigue & Safety Matting - Dry Areas Modular Matting Cushion Ease Solid™ ESD Nitrile FR

## General

Brand	Notrax
Category	Dry Areas Modular Matting
Product Number	661
Product Family	Industrial & Commercial Matting
Product Group	Ergonomic, Anti-fatigue & Safety Matting
Product Name	Cushion Ease Solid™ ESD Nitrile FR
Recommended use	For placement in ESD assembly lines, picking, packing and logistics warehouses, individual work stations.
Series	Cushion-Ease®
Shipping Location	Achterzeedijk 57, Unit 15, Barendrecht 2992SB, The Netherlands
Type	Dry Areas - Heavy Duty Modular Rubber Mats
Update trigger	20210310-1301
Usage Intensity	Heavy duty

## Sustainability

REACH	Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).
Recycled	True
Sustainability	Recyclable material
Warranty	1

## Tests

Abrasion Resistance 1000	2.2% (5000 cycles)
ESD Rg	Rp 10 <sup>6</sup> - 10 <sup>9</sup> Ω
ESD Rp	Rp 10 <sup>6</sup> - 10 <sup>9</sup> Ω
Fire rating EU	EN 13501-1 Bfl-S1
Fire rating US	Pass
Hardness	56 Shore A
Slip Rating	R9
Coefficient Friction Dry	0.81
Surface Flammability	Pass

# Technical Specifications

Application	Industrial Environments
Edges	Attachable bevelled edges are available
Material	Static dissipative and fire retardant nitrile rubber compound
Material Group	Nitrile rubber
Process	Compression Moulding

# Cushion Ease Solid™ ESD Nitrile FR Black

Art. nr.	Dimension (cm)	Weight (kg)	Thickness (mm)
661S0000BL	per m2	13.6	19
661S0033BL	91cm x 91cm	12.7	19

## Accessories

552 MD-X Ramp System™ Nitrile	INS INSTALLATION	551 MD Ramp System™ Nitrile	057 ESD Mat Cleaner
056 ESD Wrist Band	052 ESD Common Grounding Cord	055 ESD Heel Grounder	051 ESD Floor Grounding Cord
054 ESD Earth Bonding Plug	053 ESD Coil Cord		